

Beaulieu  
Needle  
Felt

**Cartrim**  
AUTOMOTIVE



### Shaping sustainable living, together

As a global family business, we develop and co-create – in an innovative, entrepreneurial and sustainable way – flooring and material solutions to enhance the quality of living and working for every generation.

We are taking practical steps to reduce our environmental footprint, while looking after our people and the ones around us, and doing business in a transparent, ethical way.



A division of  
**Beaulieu International Group**  
BFS Europe NV  
Groenedreef 15A, 9770 Kruisem  
[www.beaulieu-needlefelt.com](http://www.beaulieu-needlefelt.com)

DNF.RO.MAR.15a/3/01-04-2024  
Update: 04-2024

### Technical specifications

Manufacturing process	DIN 61151	<b>Needle felt</b>
Pile composition	-	<b>50% PP &amp; 50% PET</b>
Surface structure	-	<b>Dilour</b>
Backing	ISO 2424	<b>Unbacked</b>
Pile weight	ISO 8453	<b>320 g/m<sup>2</sup></b>
Total weight	ISO 8453	<b>320 g/m<sup>2</sup></b>
Pile height	ISO 1765	<b>3 mm</b>
Total height	ISO 1765	<b>3 mm</b>
Roll width	-	<b>2 m</b>
Roll length	-	<b>40 m</b>
Production	-	<b>Non woven</b>
Subcategory	-	<b>For trimming</b>



Colours may slightly vary from batch to batch.  
Characteristics in line with EN 1307 standards.  
We reserve the right to alter technical specifications.  
Protection foil is not suitable in humid conditions.  
© Beaulieu International Group



# Cartrim

Colour	2 m
0200	✓
0907	✓
0913	✓
0926	✓
0952	✓
5104	✓

