

As a global family business, we develop and co-create – in an innovative, entrepreneurial and sustainable way – flooring and material solutions to enhance the quality of living and working for every generation.

We are taking practical steps to reduce our environmental footprint, while looking after our people and the ones around us, and doing business in a transparent, ethical way.



A division of Beaulieu International Group BFS Europe NV Groenedreef 15A, 9770 Kruisem www.beaulieu-needlefelt.com

DNF.RO.MAR.15a/3/01-04-2024 Update: 04-2024





Technical specifications

Manufacturing process	DIN 61151	Needle felt
Pile composition	-	100% PA
Surface structure	-	5/64" cutpile tuft
Backing	ISO 2424	Action back
Pile weight	ISO 8453	450 g/m²
Total weight	ISO 8453	1265 g/m²
Pile height	ISO 1765	4.5 mm
Total height	ISO 1765	5 mm
Roll length	-	30 m
Fire classification	EN 13501-1	Cfl-s1





Colours may slightly vary from batch to batch.
Characteristics in line with EN 1307 standards.
We reserve the right to alter technical specifications.
Protection foil is not suitable in humid conditions.

© Beaulieu International Group

Las Vegas

Colour	2 m	4 m
1703	√	
1730	√	
1733		
1734		
2021	√	
2709	√	
2792	√	
2794		
2795	√	
2796	√	
2797	√	
3032	√	
3711	√	
4717		

Colour	2 m	4 m
4750		
4767		
4780		
5770		
5771		
5775		
5776		
5777		
5778		
5779		√
6721		√
6722		√
7744		√

