







Technical specifications

Manufacturing process	DIN 61151	Needle felt
Pile composition	-	100% PP
Surface structure	-	Flat
Backing	ISO 2424	Precoat
Pile weight	ISO 8453	250 g/m²
Total weight	ISO 8453	610 (with foil: 635) g/m²
Pile height	ISO 1765	0 mm
Total height	ISO 1765	2.5 mm
Roll length	-	30 m
Fire classification	EN 13501-1	Cfl-s1





Colours may slightly vary from batch to batch. Characteristics in line with EN 1307 standards. We reserve the right to alter technical specifications. Protection foil is not suitable in humid conditions. © Beaulieu International Group

Plat

	WITH	WITHOUT FOIL		WITH FOIL	
Colour	1m	2 m	1m	2 m	
1333*					
1394*				√	
2340*					
2802*					
2964*				√	
4290*				√	
4721*				√	
4849*					
4870					
4871*					
4872*					
4873*				√	
4874*				√	
4875*					
4876				√	
4877*				√	
4878*				✓	
4879*				√	
4880*				√	
4881*				✓	

	WITHOUT FOIL		WITH FOIL	
Colour	1m	2 m	1m	2 m
4882*				
4893				
4894*				
4896				
4897				
4899				
4912*				
4914				
4950*				
4959*				
4961				
4962				
4963				
4964*	\checkmark			✓
4965*				√
4966*				√
4968*				✓
4969*				✓
4980*				√
4981*				✓

