**Beaulieu** Needle Felt







As a global family business, we develop and co-create – in an innovative, entrepreneurial and sustainable way – flooring and material solutions to enhance the quality of living and working for every generation.

We are taking practical steps to reduce our environmental footprint, while looking after our people and the ones around us, and doing business in a transparent, ethical way.



A division of Beaulieu International Group BFS Europe NV Groenedreef 15A, 9770 Kruisem www.beaulieu-needlefelt.com

DNF.RO.MAR.15a/3/01-04-2024 Update: 04-2024



















## **Technical specifications**

Manufacturing process	DIN 61151	Needle felt
Pile composition	-	100% PP
Surface structure	-	Flat
User class	-	33
Backing	ISO 2424	Resine
Pile weight	ISO 8453	750 g/m²
Total weight	ISO 8453	900 g/m²
Pile height	ISO 1765	0 mm
Total height	ISO 1765	5 mm
Roll length	-	30 m
Fire classification	EN 13501-1	Cfl-s1







Colours may slightly vary from batch to batch. Characteristics in line with EN 1307 standards. We reserve the right to alter technical specifications. Protection foil is not suitable in humid conditions. © Beaulieu International Group

## Xeno

Colour	2 m	4 m
1153	<b>✓</b>	<b>√</b>
1888	<b>✓</b>	<b>✓</b>
2216	<b>✓</b>	<b>√</b>
2236	<b>√</b>	<b>✓</b>
2274	<b>✓</b>	<b>✓</b>
2531	<b>✓</b>	<b>✓</b>
2860	<b>✓</b>	<b>✓</b>
2980	<b>✓</b>	<b>✓</b>
2988	<b>✓</b>	<b>✓</b>
3353	<b>✓</b>	<b>✓</b>
5539	<b>✓</b>	<b>✓</b>
5546	<b>✓</b>	<b>✓</b>
6888	<b>✓</b>	<b>✓</b>



