

Nature is a series of intricate cycles. Every ending starts a new beginning... It's time to rethink our connection with nature and close the loop! Introducing Rewind, the ultimate recyclable flooring solution. Rewind is stylish, durable and sustainable.

Produced using **zero latex**, **zero water** and with just **a fraction of energy use**. Rewind delivers significantly **lower carbon emissions** compared to traditional flooring.

And just like in nature, not a single fiber goes to waste. Rewind is made from only one material, so every carpet can be easily recycled and given a new life.

Rethink. Reinvent. Rewind.





## A division of Beaulieu International Group BFS Europe NV

Groenedreef 15A, 9770 Kruisem www.beaulieu-needlefelt.com

DNF.RO.MAR.15a/3/01-04-2024 Update: 04-2024

















## **Technical specifications**

| Manufacturing process  | DIN 61151   | Needle felt               |
|------------------------|-------------|---------------------------|
| Pile composition       | -           | 100% PP                   |
| Surface structure      | -           | Rib                       |
| User class             | -           | 32                        |
| Backing                | ISO 2424    | None - latex free         |
| Pile weight            | ISO 8453    | 900 g/m <sup>2</sup>      |
| Total weight           | ISO 8453    | 900 g/m <sup>2</sup>      |
| Pile height            | ISO 1765    | 2 mm                      |
| Total height           | ISO 1765    | 6 mm                      |
| Roll length            | -           | 30 m                      |
| Impact noise reduction | -           | 22 dB                     |
| Permanent anti-static  | ISO 6356    | ≤ 2kV                     |
| Thermal resistance     | ISO 8302    | 0,0972 m <sup>2</sup> K/W |
| Resistance to rubbing  | ISO 105-X12 | ≥5                        |
| Prodis GUT Certificate | -           | 943358A6                  |
| Fire classification    | EN 13501-1  | Bfl-s1                    |





Colours may slightly vary from batch to batch. Characteristics in line with EN 1307 standards. We reserve the right to alter technical specifications. Protection foil is not suitable in humid conditions. © Beaulieu International Group

## REWIND 900 RIB MC

| Colour | 2 m      | 4 m      |
|--------|----------|----------|
| 1098   | <b>✓</b> | <b>√</b> |
| 2077   | <b>✓</b> | <b>✓</b> |
| 2158   | <b>✓</b> | <b>✓</b> |
| 2190   | <b>✓</b> | <b>✓</b> |
| 2225   | <b>✓</b> | <b>✓</b> |
| 2241   | <b>✓</b> | <b>✓</b> |
| 2266   | <b>✓</b> | <b>√</b> |
| 3088   | <b>✓</b> | <b>✓</b> |

| Colour | 2 m      | 4 m      |
|--------|----------|----------|
| 5100   | <b>✓</b> | <b>√</b> |
| 5131   | <b>✓</b> | <b>✓</b> |
| 5151   | <b>✓</b> | <b>√</b> |
| 6099   | <b>✓</b> | <b>✓</b> |
| 6125   | <b>✓</b> | <b>√</b> |
| 7001   | <b>✓</b> | <b>√</b> |
| 7055   | <b>✓</b> | <b>√</b> |
| 7104   | <b>/</b> | <b>/</b> |

