

Beaulieu  
Needle  
Felt

# Expotop

EVENT



## Shaping sustainable living, together

As a global family business, we develop and co-create – in an innovative, entrepreneurial and sustainable way – flooring and material solutions to enhance the quality of living and working for every generation.

We are taking practical steps to reduce our environmental footprint, while looking after our people and the ones around us, and doing business in a transparent, ethical way.



A division of  
Beaulieu International Group  
BFS Europe NV  
Groenedreef 15A, 9770 Kruisem  
www.beaulieu-needlefelt.com

DNF.RO.MAR.15a/3/01-04-2024  
Update: 04-2024



## Technical specifications

Manufacturing process	DIN 61151	PVC
Backing	ISO 2424	PVC
Total thickness	-	2,4 mm
Total weight	ISO 8453	1350 g/m <sup>2</sup>
Roll length	-	30 m
Light stability	-	> 6
Dimensional stability	-	< 0,40%
Underfloor heating	-	Suitable
Residual indentation	-	< 0,35 mm
Slip resistance	-	R10
Fire classification	EN 13501-1	Bfl-s1



Colours may slightly vary from batch to batch.  
Characteristics in line with EN 1307 standards.  
We reserve the right to alter technical specifications.  
Protection foil is not suitable in humid conditions.  
© Beaulieu International Group

# Expotop

Colour	2 m
0711	✓
0834	✓
0910	✓
0955	✓
1010	✓
2098	✓

