

Beaulieu
Needle
Felt

Pemba

OUTDOOR



Shaping sustainable living, together

As a global family business, we develop and co-create – in an innovative, entrepreneurial and sustainable way – flooring and material solutions to enhance the quality of living and working for every generation.

We are taking practical steps to reduce our environmental footprint, while looking after our people and the ones around us, and doing business in a transparent, ethical way.



A division of
Beaulieu International Group
BFS Europe NV
Groenedreef 15A, 9770 Kruisem
www.beaulieu-needlefelt.com

DNF.RO.MAR.15a/3/01-04-2024
Update: 04-2024



Technical specifications

Manufacturing process	DIN 61151	Needle felt
Pile composition	-	100% synthetic
Surface structure	-	Flat
Backing	ISO 2424	Precoat
Pile weight	ISO 8453	280 g/m²
Total weight	ISO 8453	800 g/m²
Pile height	ISO 1765	2 mm
Total height	ISO 1765	3 mm
Roll length	-	50 m (1,33 m) 75 m (2 m - 4 m)
Fire classification	EN 13501-1	Efl



Colours may slightly vary from batch to batch.
Characteristics in line with EN 1307 standards.
We reserve the right to alter technical specifications.
Protection foil is not suitable in humid conditions.
© Beaulieu International Group

Pemba

Colour	1,33 m	2 m	4 m
0630	✓	✓	✓



0630
Moos