

2199H

100 MELT FLOW IMPACT COPOLYMER POLYPROPYLENE FOR INJECTION MOLDING

Product Description and Applications:

Pinnacle Polymers Polypropylene 2199H is made via UNIPOLTM PP technology, which utilizes gas-phase fluidized bed reactors with a high activity catalyst system to ensure uniform physical properties and lottolot consistency.

This controlled rheology copolymer is intended for use in thin wall injection molded packaging, housewares and consumer products applications. Ultra High Melt Flow dramatically improves cycle- times without forfeiting properties. Contains nucleator and antistat.

Features:

The 2199H product provides:

- Excellent cycle-time
- · Very high melt flow
- Excellent mold release
- Superior processability
- Excellent lot-to-lot consistency

Typical Properties

Property	Units	Test Method
Melt Flow Rate	100 g/10 min.	ATSM D1238
Density at 23°C	900 kg/m	ISO 1183-1
Tensile Yield Strength, at 50 mm/min	17.7 MPa	ISO 527
Tensile Strain at Yield	7.6%	ISO 527
Flexural Modulus	1069 MPa	ISO 178
Notched Izod Impact Strength, at 23°C	1.3 ft-lb/in	ATSM D256
Charpy Impact Strength, at 23°C	8.5 kJ/m²	ISO 179-1
Gardner Impact at -30°C	24 J	ATSM D5420

FDA, EU 10/2011/EC, and SDS documents are available on our website at: https://pinnaclepolymers.com/documents-datasheets/regulatory-documents

UNIPOL is a trademark of W. R. Grace and Co.

Technical data contained herein is furnished without fee or obligation, and is given and accepted at recipient's sole risk. Since conditions of use may vary and are beyond our control. Pinnacle Polymers makes no representation about and is not responsible or liable for the accuracy or reliability of data, nor for toxicological effects, industrial hygiene requirements, or other matters associated with particular application of any product described herein. Pinnacle Polymers disclaims any warranty, expressed or implied, regarding the information contained herein, including the implied warranty of merchantability of fitness for a particular purpose. 012924