

As a global family business, we develop and co-create – in an innovative, entrepreneurial and sustainable way – flooring and material solutions to enhance the quality of living and working for every generation.

We are taking practical steps to reduce our environmental footprint, while looking after our people and the ones around us, and doing business in a transparent, ethical way



A division of Beaulieu International Group BFS Europe NV Groenedreef 15A, 9770 Kruisen www.beaulieu-needlefelt.com

DNF.RO.MAR.15α/3/01-04-2024





Technical specifications

| Manufacturing process | DIN 61151 | Needle felt |
|-----------------------|------------|----------------|
| Pile composition | - | 100% synthetic |
| Surface structure | - | Dilour |
| Backing | ISO 2424 | Precoat |
| Pile weight | ISO 8453 | 330 g/m² |
| Total weight | ISO 8453 | 850 g/m² |
| Pile height | ISO 1765 | 3 mm |
| Total height | ISO 1765 | 3.5 mm |
| Roll length | - | 45 m |
| Fire classification | EN 13501-1 | Efl |





Colours may slightly vary from batch to batch. Characteristics in line with EN 1307 standards. We reserve the right to alter technical specifications. Protection foil is not suitable in humid conditions. © Beaulieu International Group

Cricket

| Colour | 2 m | 4 m |
|--------|-----|-----|
| 0600 | | |

