

SPECIFICATIONS

STYLE NAME: PARKWAY PRO CLICK	APPROX. WEIGHT PER CARTON: 39.66 LBS. PLANK 39.75 LBS. TILE
LOCKING SYSTEM: VALINGE 2G	CARTON SIZE: 7.68" W X 48.43" L X 2.36" H PLANK 12.4" W X 24.6" L X 2.56" H TILE
FINISH: 12 MIL WEAR LAYER ALL OVER EMBOSS	CARTONS PER PALLET: 65 PLANK 66 TILE
BEVEL: 4 SIDED MICRO BEVEL	SQUARE FEET PER PALLET: 1,755 SQ. FT. PLANK 1,782 SQ. FT. TILE
NOMINAL PRODUCT THICKNESS: 4.4 MM TOTAL (3.4 MM + 1 MM PAD)	APPROX. WEIGHT PER PALLET: 2,578.09 LBS. PLANK 1,190.2 LBS. TILE
NOMINAL PLANK SIZE: 6.95" W X 47.64" L X 0.17" H NOMINAL TILE SIZE: 11.93" W X 23.9" L X 0.17" H	PALLETS PER 40 FT. CONTAINER: 21 PLANK 21 TILE
PIECES PER CARTON: 12 PLANK 14 TILE	SQUARE FEET PER 40 FT. CONTAINER: 36,855 SQ. FT. PLANK 37,422 SQ. FT. TILE
SQUARE FEET PER CARTON: 27.60 SQ. FT. PLANK 27.72 SQ. FT. TILE	APPROX. WEIGHT PER 40 FT. CONTAINER: 54,139.89 LBS. PLANK 24,994.2 LBS. TILE
	COUNTRY OF ORIGIN: MANUFACTURED IN VIETNAM

WARRANTIES

LIFETIME RESIDENTIAL WEAR, FADE, STAIN, & JOINT

10 YEAR LIGHT COMMERCIAL WEAR, FADE, STAIN, & JOINT

CARE & MAINTENANCE

GENERAL MAINTENANCE SHOULD INCLUDE PLACING NON-STAINING WALK-OFF MATS AT ALL EXTERIOR ENTRANCES TO REDUCE TRACKED IN SOIL. USE A SOFT BRISTLE BROOM TO SWEEP OR VACUUM WITHOUT A BEATER BAR TO REMOVE DIRT, GRIT OR SAND.

FOR HEAVILY SOILED AREAS, USE A NON-ABRASIVE NEUTRAL PH CLEANER SPECIALLY FORMULATED FOR USE WITH LVP AND A MICROFIBER MOP.

PERFORMANCE

FLOOR SCORE CERTIFIED	ASTM C1028 SCOF: DRY 0.63
ORTHO PHTHALATE FREE	ASTM F970 STATIC LOAD: PASSES
ASTM E648 CRITICAL RADIANT FLUX: CLASS 1	ASTM F137 FLEXIBILITY: PASSES 75 MM MANDREL
ASTM E662 SMOKE DENSITY: UNDER 450	ASTM F925 CHEMICAL RESISTANCE: PASSES
ASTM F1515 LIGHT STABILITY: < 8.0 DELTA E - PASSES	ASTM F1514 HEAT STABILITY DELTA E < 8.0: PASSES
ASTM F2199 DIMENSIONAL STABILITY HEAT: PASSES	ASTM D4060 ABRASION RESISTANCE: 17,000 CYCLES
AATCC 134 (STEP) ELECTROSTATIC: 0.8 K.V. OR LOWER	

INSTALLATION

END USE: RESIDENTIAL, LIGHT COMMERCIAL	SUITABLE GRADE LEVEL: ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
INSTALLATION METHOD: FLOAT	RADIANT FLOOR HEAT COMPATIBLE: FLOOR SURFACE TEMPERATURE NOT TO EXCEED 80°F

PLANK DESIGN	PART NUMBER	EAN / UPC NUMBER	TILE DESIGN	PART NUMBER	EAN / UPC NUMBER
ASH	60001575	190670020993	ARCTIC	60001878	190670029446
BARK	60001576	190670021006	CINDER	60001875	190670029415
BARLEY	60001577	190670021013	CLIFF	60001876	190670029422
CHESTNUT	60001578	190670021020	SANDSTONE	60001877	190670029439
CINNAMON	60001579	190670021037			
GINGER	60001580	190670021044			
GUNSTOCK	60001581	190670021051			
SAND	60001582	190670021068			