

SPECIFICATIONS

STYLE NAME: PARKWAY PRO DRY BACK	CARTON SIZE: 48.43"W X 7.68"L X 1.18"H PLANK 12.40"W X 24.61"L X 1.57"H TILE
FINISH: 12 MIL WEAR LAYER (0.3 MM) MEDIUM EMBOSS	CARTONS PER PALLET: 72 PLANK 72 TILE
BEVEL: SQUARE EDGES	SQUARE FEET PER PALLET: 2,610.72 SQ. FT. PLANK 2,596.32 SQ. FT. TILE
NOMINAL PRODUCT THICKNESS: 2.0 MM (0.079")	APPROX. WEIGHT PER PALLET: 1,985.04 LBS. PLANK 1,949.99 LBS. TILE
NOMINAL PLANK SIZE: 7.25"W X 48"L x 0.079"H NOMINAL TILE SIZE: 12.01"W X 24.02"L x 0.079"H	PALLETS PER 40 FT. CONTAINER: 27 PLANK 24 TILE
PIECES PER CARTON: 15 PLANK 18 TILE	SQUARE FEET PER 40 FT. CONTAINER: 69,984 SQ. FT. PLANK 62,208 SQ. FT. TILE
SQUARE FEET PER CARTON: 36.26 SQ. FT. PLANK 36.06 SQ. FT. TILE	APPROX. WEIGHT PER 40 FT. CONTAINER: 53,596.08 LBS. PLANK 42,799.76 LBS. TILE
APPROX. WEIGHT PER CARTON: 27.01 LBS. PLANK 27.46 LBS. TILE	COUNTRY OF ORIGIN: MANUFACTURED IN VIETNAM

WARRANTIES

LIFETIME LIMITED RESIDENTIAL WEAR,
MANUFACTURING DEFECT, FADE, STAIN,
WATERPROOF

10 YEAR LIGHT COMMERCIAL WEAR,
2 YEAR MANUFACTURING DEFECT

CARE & MAINTENANCE

GENERAL MAINTENANCE SHOULD
INCLUDE PLACING NON-STAINING WALK-
OFF MATS AT ALL EXTERIOR ENTRANCES
TO REDUCE TRACKED IN SOIL. USE A
SOFT BRISTLE BROOM TO SWEEP OR
VACUUM WITHOUT A BEATER BAR TO
REMOVE DIRT, GRIT OR SAND.

FOR HEAVILY SOILED AREAS, USE A NON-
ABRASIVE NEUTRAL PH CLEANER AND A
MICROFIBER MOP.

PERFORMANCE

FLOOR SCORE CERTIFIED	ASTM C1028 SCOF: DRY 0.63
ORTHO PHTHALATE FREE	ASTM F970 STATIC LOAD: PASSES
ASTM E648 CRITICAL RADIANT FLUX: CLASS 1	ASTM F137 FLEXIBILITY: PASSES 6 MM MANDREL
ASTM E662 SMOKE DENSITY: UNDER 450	ASTM F925 CHEMICAL RESISTANCE: PASSES
ASTM F1515 LIGHT STABILITY: < 8.0 DELTA E - PASSES	ASTM F1514 HEAT STABILITY DELTA E < 8.0: PASSES
ASTM F2199 DIMENSIONAL STABILITY HEAT: PASSES	ASTM D4060 ABRASION RESISTANCE: 20,000 CYCLES
AATCC 134 (STEP) ELECTROSTATIC: 0.4 K.V. OR LOWER	

INSTALLATION

END USE: RESIDENTIAL, LIGHT COMMERCIAL	SUITABLE GRADE LEVEL: ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
INSTALLATION METHOD: DIRECT GLUE DOWN	RADIANT FLOOR HEAT COMPATIBLE: FLOOR SURFACE TEMPERATURE NOT TO EXCEED 80°F
INSTALLATION SUNDRIES AS REQUIRED: BEAUFLOOR 4N1 MULTIPURPOSE ADHESIVE	

PLANK DESIGN PART NUMBER EAN / UPC NUMBER TILE DESIGN PART NUMBER EAN / UPC NUMBER

ASH	60001376	190670015951	ARCTIC	60001883	190670029484
BARK	60001377	190670015968	CINDER	60001880	190670029453
BARLEY	60001378	190670015975	CLIFF	60001881	190670029460
CHESTNUT	60001379	190670015982	SANDSTONE	60001882	190670029477
CINNAMON	60001380	190670015999			
GINGER	60001381	190670016002			
GUNSTOCK	60001382	190670016019			
SAND	60001383	190670016026			