

SPECIFICATIONS

STYLE NAME: INNOVIOUS CURIO	APPROX. WEIGHT PER CARTON: 48.55 LBS.
LOCKING SYSTEM: i4F Standard	CARTON SIZE: 7.60"W X 59.49" L X 2.09"H
FINISH: 20 MIL WEAR LAYER EMBOSS IN REGISTER (EIR)	CARTONS PER PALLET: 55
BEVEL: PAINTED BEVEL	SQUARE FEET PER PALLET: 1,257.85 SQ. FT.
NOMINAL PRODUCT THICKNESS: 6 MM TOTAL (5 MM + 1 MM PAD)	APPROX. WEIGHT PER PALLET: 2,733.73 LBS.
NOMINAL PLANK SIZE: 7.00" W X 58.74"L x 0.23" H	PALLETS PER 40 FT. CONTAINER: 15
UNIQUE PLANKS PER SKU: 5	SQUARE FEET PER 40 FT. CONTAINER: 18,867.75 SQ. FT.
PLANKS PER CARTON: 8	APPROX. WEIGHT PER 40 FT. CONTAINER: 41,005 LBS.
SQUARE FEET PER CARTON: 22.87 SQ. FT.	COUNTRY OF ORIGIN: MANUFACTURED IN VIETNAM

PERFORMANCE

FLOOR SCORE CERTIFIED	ASTM C1028 SCOF: DRY 0.66, WET 0.61
ORTHO PHTHALATE FREE	ASTM F970 STATIC LOAD: PASSES ≤ 250 PSI
ASTM E648 CRITICAL RADIANT FLUX: CLASS 1	ASTM F137 FLEXIBILITY: PASSES 115 MM MANDREL
ASTM E662 SMOKE DENSITY: UNDER 450	ASTM F925 CHEMICAL RESISTANCE: PASSES
ASTM F1515 LIGHT STABILITY: < 8.0 DELTA E – PASSES	ASTM F1514 HEAT STABILITY DELTA E < 8.0: PASSES
ASTM F2199 DIMENSIONAL STABILITY HEAT: PASSES	ASTM D4060 ABRASION RESISTANCE: 43,700 CYCLES
AATCC 134 (STEP) ELECTROSTATIC: 1.5 K.V. OR LOWER	ASTM D2047 COEFFICIENT OF FRICTION: DRY 0.88
ASTM E492: IIC 74	ASTM E413: STC 71

INSTALLATION

END USE: RESIDENTIAL, LIGHT COMMERCIAL	SUITABLE GRADE LEVEL: ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST
INSTALLATION METHOD: FLOAT	RADIANT FLOOR HEAT COMPATIBLE: FLOOR SURFACE TEMPERATURE NOT TO EXCEED 80°F

DESIGN

PART NUMBER

EAN / UPC NUMBER

EVER ELM 029L	60002065	190670034457
SOL ELM 149L	60002066	190670034464
REVEL ELM 139L	60002067	190670034471
TOMMIE ELM 991M	60002068	190670034488
SALEM ELM 464D	60002069	190670034495
BRIAR PINE 910L	60002070	190670034501
COVE PINE 246M	60002071	190670034518
CYPRESS PINE 699D	60002072	190670034525
MARIGOLD OAK 269L	60002073	190670034532
FLINT OAK 990M	60002074	190670034549
CALLAWAY OAK 264M	60002075	190670034556
BRIGHTON OAK 996M	60002076	190670034563

WARRANTIES

LIFETIME RESIDENTIAL WEAR, FADE,
STAIN, & JOINT

15 YEAR LIGHT COMMERCIAL WEAR,
FADE, STAIN, & JOINT

CARE & MAINTENANCE

GENERAL MAINTENANCE SHOULD
INCLUDE PLACING NON-STAINING WALK-
OFF MATS AT ALL EXTERIOR ENTRANCES
TO REDUCE TRACKED IN SOIL. USE A
SOFT BRISTLE BROOM TO SWEEP OR
VACUUM WITHOUT A BEATER BAR TO
REMOVE DIRT, GRIT OR SAND.

FOR HEAVILY SOILED AREAS, USE A
NON-ABRASIVE NEUTRAL PH CLEANER
SPECIALLY FORMULATED FOR USE WITH
LVP AND A MICROFIBER MOP.