SPECIFICATIONS

STYLE NAME: **OMEGA+**	BACKING TYPE: **POWERBAC**
FINISH: **PU LACQUER**	AVAILABLE WIDTH: **12'**
PATTERN REPEAT: **REFER TO DESIGN CHART BELOW**	STANDARD ROLL LENGTH (TOLERANCES APPLY): **92'**
NOMINAL WEAR LAYER THICKNESS: **10 MILS (0.25 MM)**	WEIGHT PER SQUARE YARD: **3.779 LBS/SQ. YD.**
NOMINAL PRODUCT THICKNESS: **140 GAUGE (3.55 MM)**	COUNTRY OF ORIGIN: **MANUFACTURED IN USA OF GLOBAL COMPONENTS**

PERFORMANCE

FLOORSCORE CERTIFIED	ASTM F963 HEAVY METAL CONTENT ANALYSIS: **PASSES**
CPSC-CH-C1001-09.3 PHTHALATES: **MEETS CPSIA GUIDE**	ASTM F970 STATIC LOAD: **PASSES**
ASTM E648 CRITICAL RADIANT FLUX: **UNDER 450**	ASTM D4060 ABRASION RESISTANCE: **PASSES**

INSTALLATION

END USE: **RESIDENTIAL**	SUITABLE GRADE LEVEL: **ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST**
INSTALLATION METHOD: **DIRECT GLUE DOWN OR LOOSE LAY UP TO 25 SQ. YD (225 SQ. FT.)**	INSTALLATION SUNDRIES AS NEEDED: **BEAUFLOR 4N1 MULTIPURPOSE ADHESIVE, BEAUFLOR CV SEAM SEALER**

DESIGN	PART NUMBER	PATTERN REPEAT
ASTRID OYSTER 179M	50046719	78.28" x 59.10"
ASTRID SAND 173M	50047133	78.28" x 59.10"
COSMOS LATTE 616M	50046714	39.37" x 39.37"
COSMOS SMOKE 191M	50047125	39.37" x 39.37"
COSMOS STONE 976D	50047124	39.37" x 39.37"
EARTHBOUND FOSSIL 630M	50047138	39.37" x 39.37"
ECLIPSE AMBER 637D	50046718	39.37" x 39.37"
ECLIPSE PEARL 170L	50046717	39.37" x 39.37"
MOONWOOD BURLAP 166M	50047136	39.37" x 59.07"
MOONWOOD CLOUD 769M	50047137	39.37" x 59.07"
NEBULA ASH 919M	50046715	39.37" x 39.37"
ODYSSEY OAK COFFEE 664D	50047117	39.37" x 59.10"
ODYSSEY OAK OAT 629M	50046720	39.37" x 59.10"
PANDORA BONE 710M	50046721	78.28" x 59.10"
PANDORA MINK 670M	50046722	78.28" x 59.10"
STARDUST CHARCOAL 971M	50047130	39.37" x 39.37"
STARDUST GINGER 621M	50046723	39.37" x 39.37"
STARDUST SILVER 097M	50047132	39.37" x 39.37"
STELLAR OAK CREAM 176L	50047122	78.28" x 59.10"
STELLAR OAK FOG 767M	50047121	78.28" x 59.10"
STELLAR OAK PEANUT 616M	50047120	78.28" x 59.10"
VEGA OAK PECAN 693D	50046716	39.37" x 59.10"

WARRANTIES

25 YEAR LIMITED RESIDENTIAL WEAR

CARE & MAINTENANCE

GENERAL MAINTENANCE SHOULD INCLUDE PLACING NON-STAINING WALK-OFF MATS AT ALL EXTERIOR ENTRANCES TO REDUCE TRACKED IN SOIL. USE A SOFT BRISTLE BROOM TO SWEEP OR VACUUM WITHOUT A BEATER BAR TO REMOVE DIRT, GRIT OR SAND.

FOR HEAVILY SOILED AREAS, USE A NON-ABRASIVE NEUTRAL PH CLEANER WITH A MICROFIBER MOP.