

**SPECIFICATIONS**

|                                                        |                                                                    |
|--------------------------------------------------------|--------------------------------------------------------------------|
| STYLE NAME: <b>METRO+</b>                              | BACKING TYPE: <b>POWERBAC</b>                                      |
| FINISH: <b>PU LACQUER</b>                              | AVAILABLE WIDTH: <b>12'</b>                                        |
| PATTERN REPEAT: <b>REFER TO DESIGN CHART BELOW</b>     | STANDARD ROLL LENGTH (TOLERANCES APPLY): <b>140 FT.</b>            |
| NOMINAL WEAR LAYER THICKNESS: <b>10 MILS (0.25 MM)</b> | WEIGHT PER SQUARE YARD: <b>2.39 LBS/SQ. YD.</b>                    |
| NOMINAL PRODUCT THICKNESS: <b>55 GAUGE (1.4 MM)</b>    | COUNTRY OF ORIGIN: <b>MANUFACTURED IN USA OF GLOBAL COMPONENTS</b> |

**PERFORMANCE**

|                                                         |                                                       |
|---------------------------------------------------------|-------------------------------------------------------|
| <b>FLOORSCORE CERTIFIED</b>                             | ASTM F963 HEAVY METAL CONTENT ANALYSIS: <b>PASSES</b> |
| CPSC-CH-C1001-09.3 PHTHALATES: <b>MEETS CPSIA GUIDE</b> | ASTM F970 STATIC LOAD: <b>PASSES</b>                  |
| ASTM E648 CRITICAL RADIANT FLUX: <b>UNDER 450</b>       | ASTM D4060 ABRASION RESISTANCE: <b>PASSES</b>         |

**INSTALLATION**

|                                                                                        |                                                                                                       |
|----------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|
| END USE: <b>RESIDENTIAL</b>                                                            | SUITABLE GRADE LEVEL: <b>ALL GRADES WHERE EXCESSIVE MOISTURE CONDITIONS DO NOT EXIST</b>              |
| INSTALLATION METHOD: <b>DIRECT GLUE DOWN OR LOOSE LAY UP TO 25 SQ. YD/225 SQ. FT.)</b> | INSTALLATION SUNDRIES AS NEEDED: <b>BEAUFLOOR 4N1 MULTIPURPOSE ADHESIVE, BEAUFLOOR CV SEAM SEALER</b> |

**DESIGN**

**PART NUMBER**

**PATTERN REPEAT**

| DESIGN                        | PART NUMBER | PATTERN REPEAT  |
|-------------------------------|-------------|-----------------|
| BARNWOOD CROSSING COFFEE 661D | 50045946    | 39.37" X 59.06" |
| MIDLAND HICKORY OAT 679M      | 50045948    | 39.37" X 39.37" |
| MAINSTREAM OYSTER 639M        | 50045955    | 39.37" X 39.37" |
| CAPITOL OAK MINK 963M         | 50045945    | 39.37" X 39.37" |
| HERITAGE TAWNY OAK 191M       | 50064982    | 39.37" X 39.37" |
| URBAN OAK MIST 109L           | 50064984    | 39.37" X 39.37" |
| ARCTIC STONE PEARL 090L       | 50064985    | 96" X 48"       |
| STATION OAK FOSSIL 996D       | 50045943    | 39.37" X 59.06" |
| STATION OAK PEANUT 631M       | 50045944    | 39.37" X 59.06" |
| HORIZON ALDER SNOW 210L       | 50064983    | 39.37" X 39.37" |

**WARRANTIES**

10 YEAR LIMITED RESIDENTIAL WEAR

**CARE & MAINTENANCE**

GENERAL MAINTENANCE SHOULD INCLUDE PLACING NON-STAINING WALK-OFF MATS AT ALL EXTERIOR ENTRANCES TO REDUCE TRACKED IN SOIL. USE A SOFT BRISTLE BROOM TO SWEEP OR VACUUM WITHOUT A BEATER BAR TO REMOVE DIRT, GRIT OR SAND.

FOR HEAVILY SOILED AREAS, USE A NON-ABRASIVE NEUTRAL PH CLEANER WITH A MICROFIBER MOP